

QXXW.EX28387 - Centrifugal Fire Pumps, Vertical Turbine

Centrifugal Fire Pumps, Vertical Turbine

See General Information for Centrifugal Fire Pumps, Vertical Turbine

QUANTUM PUMP SYSTEMS LTD - UK

TREGONIGGIE INDUSTRIAL ESTATE, FALMOUTH, UK, TR11 4SN
FALMOUTH, TR11 4SN UNITED KINGDOM

EX28387

Rated Capacity gpm	Model Dsg	Rated Net Pressure Range psi	Approx Speed rpm	Stages
100	QVT1-100/40-6	40-44	2900	1
100	QVT1-100/40-6	61-265	2900	2-6
150	QVT1-100/40-6	40-44	2900	1
150	QVT1-100/40-6	60-263	2900	2-6
200	QVT1-100/40-6	40-43	2900	1
200	QVT1-100/40-6	56-257	2900	2-6
250	QVT1-100/40-6	40-42	2900	1
250	QVT1-100/40-6	52-250	2900	2-6
300	QVT1-150/200-17	40-235	1480	2-8
400	QVT1-150/200-17	40-227	1480	2-8
450	QVT1-150/200-17	40-225	1480	2-8
500	QVT1-150/200-17	40-221	1480	2-8
500	QVT1-150/200-17	40-241	1760	2-6
750	QVT1-200/250-22	40-313	1480	2-8
750	QVT1-150/200-17	74	1760	2
750	QVT1-150/200-17	111	1760	3
750	QVT1-150/200-17	148	1760	4
750	QVT1-150/200-17	185	1760	5
750	QVT1-150/200-17	222	1760	6
750	QVT1-200/250-22	40-58	1760	1
750	QVT1-200/250-22	75-288	1760	2-5

1000	QVT1-200/250-22	40-288	1480	2-8
1000	QVT1-200/250-22	40-54	1760	1
1000	QVT1-200/250-22	69-272	1760	2-5
1250	QVT1-250/400-28	120-147	1760	2
1250	QVT1-250/400-28	124-153	1480	3
1250	QVT1-250/400-28	165-305	1480	4-6
1250	QVT1-250/400-28	180-221	1760	3
1250	QVT1-250/400-28	240-294	1760	4
1250	QVT1-250/400-28	41-51	1480	1
1250	QVT1-250/400-28	60-74	1760	1
1250	QVT1-250/400-28	82-102	1480	2
1500	QVT1-250/400-28	115-143	1760	2
1500	QVT1-250/400-28	115-292	1480	3-6
1500	QVT1-250/400-28	173-214	1760	3
1500	QVT1-250/400-28	230-285	1760	4
1500	QVT1-250/400-28	40-49	1480	1
1500	QVT1-250/400-28	58-71	1760	1
1500	QVT1-250/400-28	77-97	1480	2
2000	QVT1-250/400-28	63	1760	1
2000	QVT1-250/400-28	125	1760	2
2000	QVT1-250/400-28	188	1760	3
2000	QVT1-250/400-28	251	1760	4
2000	QVT1-250/550-26	113-133	1760	2
2000	QVT1-250/550-26	116-132	1480	3
2000	QVT1-250/550-26	155-176	1480	4
2000	QVT1-250/550-26	170-199	1760	3
2000	QVT1-250/550-26	194-264	1480	5-6
2000	QVT1-250/550-26	227-266	1760	4
2000	QVT1-250/550-26	40-44	1480	1
2000	QVT1-250/550-26	57-66	1760	1
2000	QVT1-250/550-26	77-88	1480	2
2500	QVT1-250/550-26	61	1760	1
2500	QVT1-250/550-26	123	1760	2

2500	QVT1-250/550-26	184	1760	3
2500	QVT1-250/550-26	245	1760	4
2500	QVT1-300/860-43	100-245	1480	2-3
2500	QVT1-350/860-43	149-236	1760	2
2500	QVT1-300/860-43	50-82	1480	1
2500	QVT1-350/860-43	74-118	1760	1
3000	QVT1-300/860-43	105-235	1480	2-3
3000	QVT1-350/860-43	139-230	1760	2
3000	QVT1-350/860-43	146-222	1760	2
3000	QVT1-300/860-43	53-78	1480	1
3000	QVT1-350/860-43	69-115	1760	1
3000	QVT1-350/860-43	73-111	1760	1
3500	QVT1-350/1250-36	140-249	1480	3-4
3500	QVT1-350/1250-36	47-62	1480	1
3500	QVT1-350/1250-36	93-124	1480	2
3500	QVT1-350/1250-36	112-148	1600	2
3500	QVT1-350/1250-36	168-295	1600	3-4
3500	QVT1-350/1250-36	56-74	1600	1
4000	QVT1-350/860-43	104	1760	1
4000	QVT1-350/860-43	207	1760	2
4000	QVT1-350/1250-36	135-243	1480	3-4
4000	QVT1-350/1250-36	45-61	1480	1
4000	QVT1-350/1250-36	90-121	1480	2
4000	QVT1-350/1250-36	107-144	1600	2
4000	QVT1-350/1250-36	161-288	1600	3-4
4000	QVT1-350/1250-36	54-72	1600	1
4000	QVT1-400/1250-36	122-163	1700	2
4000	QVT1-400/1250-36	183-245	1700	3
4000	QVT1-400/1250-36	61-82	1700	1
4000	QVT1-400/1250-36	133-177	1760	2
4000	QVT1-400/1250-36	199-265	1760	3
4000	QVT1-400/1250-36	66-88	1760	1
4000	QVT1-400/1250-36	148-195	1840	2

4000	QVT1-400/1250-36	222-293	1840	3
4000	QVT1-400/1250-36	74-98	1840	1
4500	QVT1-350/1400-45	118-261	1480	2-3
4500	QVT1-350/1400-45	59-87	1480	1
4500	QVT1-350/1400-45	119-322	1630	2-3
4500	QVT1-350/1400-45	60-107	1630	1
4500	QVT1-400/1250-36	116-159	1700	2
4500	QVT1-400/1250-36	174-238	1700	3
4500	QVT1-400/1250-36	58-79	1700	1
4500	QVT1-400/1250-36	126-172	1760	2
4500	QVT1-350/1400-45	143-377	1760	2-3
4500	QVT1-400/1250-36	189-259	1760	3
4500	QVT1-400/1250-36	63-86	1760	1
4500	QVT1-350/1400-45	72-126	1760	1
4500	QVT1-400/1250-36	141-190	1840	2
4500	QVT1-400/1250-36	211-285	1840	3
4500	QVT1-400/1250-36	70-95	1840	1
5000	QVT1-350/1400-45	141-170	1480	2
5000	QVT1-350/1400-45	211-255	1480	3
5000	QVT1-350/1400-45	70-85	1480	1
5000	QVT1-350/1400-45	143-316	1630	2-3
5000	QVT1-350/1400-45	72-105	1630	1
5000	QVT1-400/1250-36	229	1700	3
5000	QVT1-400/1250-36	249	1760	3
5000	QVT1-350/1400-45	137-374	1760	2-3
5000	QVT1-350/1400-45	68-125	1760	1
5500	QVT1-350/1400-45	166-367	1760	2-3
5500	QVT1-350/1400-45	83-122	1760	1
6000	QVT1-350/1400-45	120	1760	1
6000	QVT1-350/1400-45	240	1760	2
6000	QVT1-350/1400-45	361	1760	3

Trademark and/or Tradename:



The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2020 UL LLC"